

What is claimed is:

1. A method of controlling tension in a moving web material, the method comprising steps of:
 - a) determining a modulus-of-elasticity-analog value of the moving web material,
 - b) adjusting a control system gain according to the modulus-of-elasticity-analog value of the moving web material, and
 - c) adjusting a speed of a web drive according to the control system gain.
2. The method according to claim 1 wherein the control system gain is a proportional gain.
3. The method according to claim 1 further comprising steps of:
 - a) determining a web-tension-analog value of the moving web material,
 - b) determining a web-tension error signal for the moving web,
 - c) determining a web-velocity-analog value for the moving web,
 - d) adjusting an integral gain of the controller according to the web-velocity-analog value, and
 - e) adjusting a system output according to the web-tension-error signal and the integral gain of the controller.
4. The method according to claim 1 wherein the web drive which has a speed adjusted according to the control system gain is selected from the group consisting of: an upstream drive, a downstream drive, and combinations thereof.
5. The method according to claim 1 wherein the moving web material comprises a paper web.
6. A method of adjusting an output in a process for handling a moving web material, the method comprising the steps of:
 - a) determining an error signal,
 - b) determining a web-velocity-analog value,
 - c) determining an instantaneous integral gain according to the web-velocity-analog value,
 - d) determining a modulus-of-elasticity-analog value,
 - e) determining an instantaneous proportional gain according to the modulus-of-elasticity-analog value, and
 - f) adjusting the output according to the error signal, the instantaneous integral gain and the instantaneous proportional gain.
7. The method according to claim 6 wherein the step of determining a modulus-of-elasticity-analog value comprises steps of:
 - a) determining a first web-tension-analog value of the moving web material in a first span,
 - b) determining a first web-velocity-analog value of the moving web material in the first span,
 - c) determining a second web-tension-analog value of the moving web material in a second span,

d) determining a second web-velocity-analog value of the moving web material in the second span, and

e) determining the modulus-of-elasticity-analog value of the moving web material according to the first web-tension-analog value, the second web-tension-analog value, the first web-velocity-analog value, and the second web-velocity-analog value.

8. A method of controlling a process for handling a material having a web-velocity-analog value, and a web-tension-analog value, the method comprising the steps of:

a) determining a tension set-point value,

b) determining the web-tension-analog value,

c) determining a tension error,

d) determining the web-velocity-analog value,

e) determining an instantaneous integral gain according to the web-velocity-analog value,

f) determining a modulus-of-elasticity-analog value,

g) determining an instantaneous proportional gain according to the modulus-of-elasticity-analog value, and

h) adjusting the output according to the tension error, the instantaneous proportional gain, and the instantaneous integral gain.

9. The method according to claim 8 wherein the step of determining a modulus-of-elasticity-analog value comprises steps of:

a) determining a first web-tension-analog value of the moving web material in a first span,

b) determining a first web-velocity-analog value of the moving web material in the first span,

c) determining a second web-tension-analog value of the moving web material in a second span,

d) determining a second web-velocity-analog value of the moving web material in the second span, and

e) determining the modulus-of-elasticity-analog value of the moving web material according to the first web-tension-analog value, the second web-tension-analog value, the first web-velocity-analog value, and the second web-velocity-analog value.

10. The method of claim 8 wherein the step of determining the instantaneous integral gain according to the web-velocity-analog value further comprises the steps of:

a) determining a predetermined velocity;

b) determining an integral gain for the predetermined velocity; and

c) determining the instantaneous integral gain according to the web-velocity-analog value and the predetermined velocity, and the integral gain for the predetermined velocity.

11. The method of claim 8 wherein the step of determining the instantaneous integral gain according to the web-velocity-analog value further comprises the step of:
 - a) determining the instantaneous integral gain according to the web-velocity-analog value and a length of a span of the process.
12. The method of claim 8, further comprising the steps of:
 - a) determining a lower limit modulus of elasticity;
 - b) determining an upper limit instantaneous proportional gain for the lower limit modulus of elasticity; and
 - c) setting the value of the instantaneous proportional gain equal to the upper limit instantaneous proportional gain if the determined modulus-of-elasticity-analog value is less than or equal to the lower limit modulus of elasticity.
13. The method of claim 8, further comprising the steps of:
 - a) determining an upper limit modulus of elasticity;
 - b) determining a lower limit instantaneous proportional gain for the upper limit modulus of elasticity; and
 - c) setting the value of the instantaneous proportional gain equal to the lower limit instantaneous proportional gain if the determined modulus-of-elasticity-analog value is greater than or equal to the upper limit modulus of elasticity.
14. The method of claim 8 further comprising the step of adjusting the output according to a speed draw setting.
15. The method of claim 8 further comprising the step of adjusting the speed of a drive selected from the group consisting of: an upstream drive, a downstream drive, and combinations thereof.
16. The method of claim 8 further comprising the step of selecting an auxiliary gain.
17. The method of claim 8 wherein the material comprises a paper web material.
18. A method of determining an instantaneous proportional gain in a process for handling a material having a modulus-of-elasticity-analog value, the method comprising a step of:
 - a) determining the instantaneous proportional gain according to the modulus-of-elasticity-analog value.
19. A method of controlling tension in a moving paper web material, the method comprising steps of:
 - a) determining a first web-tension-analog value of the moving web material in a first span,
 - b) determining a first web-velocity-analog value of the moving web material in the first span,
 - c) determining a second web-tension-analog value of the moving web material in a second span,
 - d) determining a second web-velocity-analog value of the moving web material in the second span,

- e) determining the modulus-of-elasticity-analog value of the moving web material according to the first web-tension-analog value, the second web-tension-analog value, the first web-velocity-analog value, and the second web-velocity-analog value,
- f) adjusting a control system gain according to the modulus-of-elasticity-analog value of the moving web material, and
- g) adjusting a speed of a web drive according to the control system gain.